

'ifeed' Feeder System Model: TTOF-400 for TTO printer.

A special designed Friction Feeder System for Thermal Transfer printer (TTO) with Double Detection function. The unique separator device is design to feed various type of materials such as laminated pouches, poly bags, cards, folded carton/box. The Double Detection function will prevent mulitple feeding of materials to avoid damage to the TTO printhead. PLC control with touch screen panel for easy setting of count quantity, count Up/Down, print delay, stop delay, double detection. Feeding and printing speed is measured by an encoder to obtain a constant print width when adjusting for different speed. The magazine hopper is capable of loading up to over 10kg of materials without separation problem. Quick and easy change over to different materials and sizes without tools.









Specification

Material size Width 80 – 400mm, Length 100 – 400mm

Materials thickness 0.10 – 5mm Magazine load Over 10kg

Printing speed Up to 60m per minute Voltage 110/240V, 50/60Hz 1Ph

Motor power 90W x 2

Control PLC

Display Touch Screen

Dimension 1000L x 700W x 1150H mm

Weight 180kg, Gross 250kg

TTO printer Allen Coding, Diagraph, VideoJet, Domino, Linx, Marken-Imaje,

Kortho, Open Date, Easyprint.

TTO type Continuous
TTO width Up to 200mm

Option

Automatic collation conveyor

Vision inspection with reject system





www.ifeedasia.com